





## IEPE Industrial Application - Integral Cable / Insulation Base

### Model NTI-15122



#### DYNAMIC

Sensitivity $\pm 5\%$	-----	200 mV/g
Measurement Range	-----	$\pm 25$ g peak
Broadband Resolution	-----	50 $\mu$ g rms
Amplitude Nonlinearity	-----	1 %
Frequency Range $\pm 5\%$	-----	0.5 – 4 kHz
$\pm 10\%$	-----	0.3 – 5 kHz
Resonance Frequency	-----	13 kHz
Transverse Sensitivity	-----	$\leq 5$ %

#### ELECTRICAL

Excitation Voltage	-----	18 - 30 VDC
Constant Current Excitation	-----	2 – 20 mA
Output Impedance	-----	$\leq 100$ $\Omega$
Output Bias Voltage	-----	12 VDC
Spectral Noise (10 Hz)	-----	6 $\mu$ g / $\sqrt{\text{Hz}}$
(100 Hz)	-----	2 $\mu$ g / $\sqrt{\text{Hz}}$
(1000 Hz)	-----	1.5 $\mu$ g / $\sqrt{\text{Hz}}$
Mounting Ground Insulation Resistance	-----	$\geq 1 \times 10^8$ $\Omega$

#### ENVIRONMENT

Maximum Vibration	-----	200 g peak
Maximum Shock	-----	500 g peak
Operation Temperature	-----	-40 to 248°F / -40 to 120°C
Sealing	-----	Welding
Base Strain Sensitivity	-----	0.001 g/ $\mu$ strain

#### PHYSICAL

Sensing Element	-----	Ceramic / Shear
Housing Material	-----	Stainless Steel
Output Connector / Position	-----	Integral Cable
Mounting Thread	-----	M5
Weight	-----	49 gram

#### ACCESORIES SUPPLIED

- Ø 3 mm x 1 m Integral Low Noise Cable with BNC Connector
- M5-M5 Mounting Stud
- Calibration Certificate

Note: Mounting thread can be changed to English 10-32 thread by request.