




## IEPE Industrial Application – TNC Output / Insulation Base

### Model NTI-14103



#### DYNAMIC

Sensitivity $\pm 10\%$	-----	100 mV/g
Measurement Range	-----	$\pm 50$ g peak
Broadband Resolution	-----	0.0001 g rms
Amplitude Nonlinearity	-----	1 %
Frequency Range $\pm 10\%$	-----	0.3 – 7 kHz
Resonance Frequency	-----	22 kHz
Transverse Sensitivity	-----	$\leq 5\%$

#### ELECTRICAL

Excitation Voltage	-----	18 - 30 VDC
Constant Current Excitation	-----	2 – 20 mA
Output Impedance	-----	$\leq 100 \Omega$
Output Bias Voltage	-----	12 VDC
Spectral Noise (10 Hz)	-----	12 $\mu\text{g} / \sqrt{\text{Hz}}$
(100 Hz)	-----	4 $\mu\text{g} / \sqrt{\text{Hz}}$
(1000 Hz)	-----	3 $\mu\text{g} / \sqrt{\text{Hz}}$
Mounting Ground Insulation Resistance	-----	$\geq 1 \times 10^8 \Omega$

#### ENVIRONMENT

Maximum Vibration	-----	400 g peak
Maximum Shock	-----	1000 g peak
Operation Temperature	-----	-40 to 248°F / -40 to 120°C
Sealing	-----	Epoxy
Base Strain Sensitivity	-----	0.001 g/ $\mu$ strain

#### PHYSICAL

Sensing Element	-----	Ceramic / Shear
Housing Material	-----	Stainless Steel
Output Connector / Position	-----	TNC / Top
Mounting Thread	-----	M5
Weight	-----	46 gram

#### ACCESSORIES SUPPLIED

- Ø 4.5 mm x 1 m Coaxial Cable with TNC / BNC Connectors
- M5-M5 Mounting Stud
- Calibration Certificate

Note: Mounting thread can be changed to English 10-32 thread by request.

